



RH系列

- 6000-10000h at 105°C
- Ultra Long life, for input filtering
- Switching power supplies
- Smoothing, Buffering, Filtering
- RoHS Compliant



Items	Characteristics								
Operating Temperature Range(°C)	-25~+105								
Voltage Range (V)	160~500								
Capacitance Range (μF)	1~470								
Capacitance Tolerance(20°C, 120Hz)	± 20%								
Leakage Current (μA)	160~500V								
	I ≤ 0.02CV+15μA After 2 minute at 20°C application of rated voltage								
	I:Max. leakage current (μA) C:Nominal Capacitance (μF) V:Rated Voltage (V)								
Dissipation Factor (20°C, 120Hz)	Rated Voltage (V)	160	200	250	350	400	420	450	500
	Tanδ(max)	0.15			0.20				0.24
Low Temperature Characteristics (Max. Impedance Ratio at 120Hz)	Rated Voltage (V)	160	200	250	350	400	420	450	500
	Z-25°C/Z+20°C	4			6				8
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied for the specified period of time at 105°C.								
	Capacitance change		≤ ± 20% of the initial value				Case Dia	Life time (h)	
	D.F.(Tanδ)		≤ 200% of specified value				φD=6.3	6000	
	Leakage current		≤ The initial specified value				φD=8	8000	
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied .								
	Capacitance change		≤ ± 20% of the initial value						
	D.F.(Tanδ)		≤ 200% of specified value						
	Leakage current		≤ 200% of specified value						

◆ Dimensions(mm)



ΦD	5	6.3	8	10	13	16	18	20	22
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5	7.5	10
Φd	0.5			0.6		0.8			
a	1.5					2.0			

◆ Frequency Coefficient

Frequency Cap(µF)	50/60HZ	120HZ	1KHZ	10KHZ	100KHZ
1.0~10	0.8	1.0	1.75	2.0	2.5
12~47	0.8	1.0	1.6	1.8	2.0
56~470	0.8	1.0	1.3	1.4	1.6

◆ Temperature Coefficient

Temperature(°C)	+70	+85	+105
Coefficient	1.80	1.40	1.00

◆ Ratings for RH Series

UR (Surge Voltage) Code (V)	Rated Capacitance (μF)	Max ESR 20°C 120Hz (Ω)	Rated Ripple Current 105°C120Hz (mA _{RMS})	Size φD×L (mm)
160(200)2C	4.7	42.30	75	6.3×12
	10	19.90	128	8×12
	15	13.30	168	8×14
	22	9.00	205	10×16
	33	6.00	255	10×20
	47	4.20	305	10×25
	56	3.20	350	13×16
	68	2.90	476	13×20
	100	2.00	632	13×25
	150	1.30	785	16×25
	220	0.90	1050	18×25
	270	0.73	1250	18×30
	330	0.60	1410	18×35
	390	0.51	1650	18×40
	470	0.42	1920	22×35
200(250)2D	4.7	42.30	72	6.3×12
	8.2	24.20	106	8×12
	10	19.90	128	8×14
	15	13.20	148	8×16
	22	9.00	205	10×16
	33	6.00	265	10×20
	47	4.20	398	10×25
	56	3.50	438	13×20
	82	2.40	560	13×25
	100	2.00	642	16×20
	150	1.30	856	16×30
	180	3.50	968	16×35
	220	0.90	1070	18×30
	270	0.73	1270	18×35
	330	0.60	1458	18×40
	390	0.51	1610	22×35
	470	0.42	1710	22×40
250(300)2E	3.3	60.30	65	6.3×12
	6.8	29.20	102	8×12
	8.2	24.20	118	8×14
	10	19.90	145	10×13
	15	13.20	165	10×16
	22	9.00	210	10×20
	27	7.30	255	10×25
	33	6.00	325	13×16
	39	5.10	380	13×20
	56	3.50	460	13×25
	68	2.90	530	16×20
	100	2.00	692	16×25
	150	1.30	868	18×30
	180	1.10	990	18×35
	220	0.90	1180	18×40
	270	0.73	1355	22×35
	330	0.60	1580	22×40
350(400)2V	2.2	120.60	55	6.3×12
	4.7	56.40	82	8×14
	6.8	39.00	115	10×13
	10	26.50	145	10×16
	15	17.60	210	10×20
	22	12.00	265	13×16
	27	9.80	332	13×20
	33	8.00	368	13×25
	47	5.60	440	16×20
	56	4.70	478	16×25
	68	3.90	575	16×30
	82	3.20	625	18×25
	100	2.60	710	18×30
	120	2.20	825	18×35
	150	1.70	975	18×40
	180	1.40	1210	22×35
	220	1.20	1350	22×40

UR (Surge Voltage) Code (V)	Rated Capacitance (μF)	Max ESR 20°C 120Hz (Ω)	Rated Ripple Current 105°C120Hz (mA _{RMS})	Size φD×L (mm)
400(450)2G	2.2	120.00	38	8×12
	4.7	56.40	80	8×14
	6.8	39.00	115	10×13
	10	26.50	145	10×16
	18	14.70	250	10×25
	22	12.00	265	13×20
	33	8.00	380	13×25
	47	5.60	460	16×25
	56	4.70	500	18×30
	68	3.90	595	16×35
400(450)2G	82	3.20	620	18×30
	100	2.60	775	18×35
	120	2.20	880	18×40
	150	1.70	995	22×35
	180	1.40	1185	22×40
420(470)W6	2.2	120.00	38	8×12
	4.7	56.40	78	8×16
	6.8	39.00	115	10×16
	10	26.50	183	10×20
	15	17.60	235	10×25
	18	14.70	255	13×20
	22	12.00	280	13×25
	33	8.00	385	16×20
	47	5.60	480	16×25
	56	4.70	535	16×30
	68	3.90	625	18×30
	82	3.20	720	18×35
	100	2.60	795	18×40
	120	2.20	895	22×35
	150	1.70	1150	22×40
450(500)2W	2.2	120.00	38	8×12
	3.3	80.40	55	8×14
	4.7	56.40	80	8×16
	6.8	39.00	115	10×16
	10	26.50	185	10×20
	15	17.60	245	10×25
	18	14.70	275	13×20
	22	12.00	300	13×25
	27	9.80	335	16×20
	33	8.00	400	16×25
	47	5.60	490	16×30
	56	4.70	535	16×35
	68	3.90	640	18×30
	82	3.20	730	18×35
	100	2.60	815	18×40
	120	2.20	880	22×35
	150	1.70	1180	22×40
500(550)2H	2.2	120.00	53	8×12
	3.3	80.40	70	8×16
	5.6	47.30	105	10×16
	8.2	32.30	135	10×20
	10	26.50	150	10×25
	15	17.60	205	13×20
	22	12.00	238	13×25
	27	9.80	270	16×20
	33	8.00	310	16×25
	47	5.60	430	16×30
	56	4.70	500	18×30
	68	3.90	545	18×35
	82	3.20	600	18×40
	100	2.60	695	22×35
	120	2.20	810	22×40